

COUNTY OF FRESNO
ADDENDUM NUMBER: THREE (3)

RFQ NUMBER: 810-5242

TRAILER MOUNTED PRESSURE WASHERS

March 6, 2014

PURCHASING USE
hrs

G:\PUBLIC\RFQ\810-5242 ADD 3.DOC

IMPORTANT: SUBMIT QUOTATION IN SEALED PACKAGE WITH QUOTATION NUMBER, CLOSING DATE AND BUYER'S NAME MARKED CLEARLY ON THE OUTSIDE TO:

COUNTY OF FRESNO, Purchasing
4525 EAST HAMILTON AVENUE, 2ND FLOOR
FRESNO, CA 93702-4599

CLOSING DATE OF BID WILL BE AT 2:00 P.M., ON MARCH 13, 2014.

QUOTES WILL BE CONSIDERED LATE WHEN THE OFFICIAL PURCHASING TIME CLOCK READS 2:00 P.M.

All quotation information will be available for review after contract award.

Clarification of specifications is to be directed to: **Craig J. Nickel**, phone (559) 600-7115, e-mail CountyPurchasing@co.fresno.ca.us, fax (559) 600-7126.

NOTE THE FOLLOWING AND ATTACHED ADDITIONS, DELETIONS AND/OR CHANGES TO THE REQUIREMENTS OF REQUEST FOR QUOTATION NUMBER: 810-5242 AND INCLUDE THEM IN YOUR RESPONSE. PLEASE SIGN AND RETURN THIS ADDENDUM WITH YOUR QUOTATION.

➤ **Please include the information on the following page in your response to RFQ No. 810-5242.**

ACKNOWLEDGMENT OF ADDENDUM NUMBER THREE (3) TO RFQ 810-5242

COMPANY NAME: _____
(PRINT)

SIGNATURE: _____

NAME & TITLE: _____
(PRINT)

ADDENDUM NO. THREE (3)
REQUEST FOR QUOTATION NUMBER 810-5242
March 6, 2014

Page 2

Single Axle Trailer

- The flooring for the heavy duty, single axle trailers shall be 1/4" metal.
- A 24" H x 53" W, 1 1/2" steel tube guard rails shall be installed (measured from the floor of the trailer) near the front of the trailer. The guard rail shall have an epoxy power coat. Five (5) steel holders shall be welded, equally spaced onto the guard rail to hold mops, squeegees and brooms.

Dual Axle Trailer

- The flooring for the dual axle trailers will be 1/4" metal with ten (10) "D" rings welded to the trailer's frame.
- A 24" H x 60" W, 1 1/2" steel tube guard rails shall be installed (measured from the floor of the trailer) near the front of the trailer. The guard rail shall have an epoxy power coat. Five (5) steel holders shall be welded, equally spaced onto the guard rail to hold mops, squeegees and brooms.

The linked diagrams of trailer mounted pressure washers are for illustrative purposes only and are not intended to infringe on the rights of the business cited nor is it intended to provide any preferential treatment. Potential bidders can view this document by going to the County website and accessing the following link:

[Trailer Mounted Pressure Washer.pdf](#)

Q1. Out trailer manufacturer is asking about the height measurement on the trailer spec. It is listed as 58" and 62" respectively. They are asking if that measurement is from the ground or from the bed of the trailer. The typical trailer sides are 12"-24" from the bed of the trailer. If the side rail measurements as spec'd are from the bed, the upcharge is significant. We have interpreted the spec'd measurement as the overall height allowed with equipment installed on it as opposed to the actual rail height.

A1. *Your interpretation is correct; the overall height specification is for installed equipment.*

Q2. The overall length of the trailer has already been clarified. The width still needs clarification. Does the width dimensions as listed, 73" and 80" respectively include the outside dimensions of the trailer or is that the desired bed width?

A2. *The two width dimensions cited includes outside dimensions (outside fender to outside fender).*